

General Improvements Specifications

Please read the details below to ensure you are installing a qualifying product(s).

Attic Insulation (Electric Heat Pump Required)

- Product can receive only one rebate from MID during its useful life period, which is defined as 20 years for attic insulation. Reapplication for rebates will not be accepted during this period.
- Rebate only available in homes with electric heat pump or resistance baseboard heating as the primary heating source.
- Must have pre-retrofit insulation level of R-11 or less.
- Final insulation level must be R-30 or greater.
- When adequate attic crawl space is not available (24 inches from ceiling joist to roof rafters), the minimum purchased insulation level must be R-19.
- Garages and other non-living areas do not qualify.

Rebate ID	Description	Rebate Amount	Unit Of Measure
HG301	Attic Insulation	\$0.17	Sq Ft

Radiant Barrier Laminated Sheeting - Roofing

- Product can receive only one rebate from MID during its useful life period, which is defined as 25 years for radiant barrier laminate sheeting. Reapplication for rebates will not be accepted during this period.
- Residence must have central air conditioning system (portable A/C units and evaporative (swamp) coolers do not qualify).
- Rebate applies to square footage of centrally air-conditioned space of the first floor only.
- Must have a radiant heat rejection rating of 95% or greater and must meet ENERGY STAR® emissivity requirements.
- Can be installed by a contractor or self-installed by the homeowner.
- Conventional architectural overhangs are allowed in the square footage.
- Maximum rebate \$500.00.

Rebate ID	Description	Rebate Amount	Unit Of Measure
HG302	Radiant Barrier Laminated Sheeting	\$0.10	Sq Ft

Radiant Barrier - Attic

- Product can receive only one rebate from MID during its useful life period, which is defined as 25 years for radiant barrier. Reapplication for rebates will not be accepted during this period.
- Must be attached to rafters or laid over existing attic insulation.
- Residence must have central air conditioning system (portable A/C units and evaporative (swamp) coolers do not qualify).
- Must have a radiant heat rejection rating of 95% or greater and must meet ENERGY STAR® emissivity requirements.
- Can be installed by a contractor or self-installed by the homeowner.
- Radiant barrier spray does not qualify for this rebate.
- Maximum rebate \$500.00.

Rebate ID	Description	Rebate Amount	Unit Of Measure
HG303	Radiant Barrier - Attic	\$0.10	Sq Ft

Radiant Barrier Facts

- A radiant barrier is a metallic foil material (usually aluminum) designed to block (reflect) radiant heat transfer.
- Radiant barriers are most commonly installed in the attic attached to the roof rafters.
- Reflectivity is the measure of how much radiant heat is reflected by a material. It is expressed as a number between 0 and 1 or as a percentage between 0 and 100%. The higher the number, the greater the material's ability to reflect radiant heat.
- Radiant barrier reflects radiant heat energy instead of trying to absorb it. What does this mean in your home? In the summer, up to 93% of heat gain is radiant. Reducing the amount of radiant heat transferred through the ceiling can reduce your cooling costs by approximately 8%.
- When installing a radiant barrier, be aware of moisture issues. To learn more, go to www.energy.gov and search "radiant barriers".